

■ AFR Headquarters

No. 399, Chuangxin 3<sup>rd</sup> Road, Tangjia, Zhuhai, China 519080  
Tel: +86 756 389 8088 Fax: +86 756 389 8080  
Email: sales@fiber-resources.com  
Web: www.fiber-resources.com

■ AFR Zhuhai (Jinding Campus)

No. 168, Jinrui 2<sup>nd</sup> Road, Tangjia, Zhuhai, China 519085  
Tel: +86 756 389 8088 Fax: +86 756 389 8080  
Email: sales@fiber-resources.com  
Web: www.fiber-resources.com

**AFR Subsidiaries**

■ AFR Milan

Via Federico Fellini, 4-San Donato Milanese (MI)-20097, Italy  
Tel: +39 02 51884 1  
Email: salesmilan@fiber-resources.com  
Web: www.afrmilan.com

■ AFR Thailand

107 Moo 18, Khlong Nueng Sub-District, Khlong Luang District, Pathum Thani 12120  
Email: salesth@fiber-resources.com  
Web: www.fiber-resources.com

■ AFR Hong Kong

Room 1002, 10/F., Ho Lik Centre, 66A Sha Tsui Road, Tsuen Wan, N.T. Hong Kong  
Tel: +852 2493 2026  
Email: sales@fiber-resources.com  
Web: www.fiber-resources.com

■ Vlink Optics Corporation

No. 399, Chuangxin 3<sup>rd</sup> Road, Tangjia, Zhuhai, China 519080  
Tel: +1 714 699 2653  
Email: isvlink@vlinkoptics.com  
Web: www.vlinkoptics.com

■ Arcadia Optronix Inc.

No. 399, Chuangxin 3<sup>rd</sup> Road, Tangjia, Zhuhai, China 519080  
Tel: +86 756 389 8338 Fax: +86 756 389 8080  
Email: sales@arcopt.com  
Web: www.arcopt.com

■ B&A Technology

Bldg 4, No.150, Cailun Rd, Pudong, Shanghai China 201210  
Tel: +86 21 5855 0298 Fax: +86 21 6129 4627  
Email: sales@baphoton.com  
Web: www.baphoton.com

# LiNbO<sub>3</sub> Modulators & Chips

2025







## COMPANY INTRODUCTION

Advanced Fiber Resources (AFR), founded in 2000, is a leading supplier of fiber optical components. With its strong R&D and design capabilities, highly efficient manufacturing process and strict quality control, AFR designs and manufactures standard and custom components, modulators, and provides contract manufacturing solutions to our customers. Our products are widely used in fiber laser, telecom, data center, fiber sensing, autonomous driving, biomedical equipment, as well as research institutes and universities around the globe. AFR's products have been sold to customers in more than 40 countries and regions worldwide.



**25**  
Years of History



**2017**  
IPO in China



**2,000**  
Employees



**115,000**  
m<sup>2</sup> Facility



**281**  
Patents



**600**  
Customers



# QUALITY

At AFR, quality is our top priority and an integral part of everything we do. The product quality management covers the entire lifecycle, from product development, to supply chain management, manufacturing, and after-sales. AFR's quality management system fulfills the requirements of ISO 9001:2015, ISO 14001:2015 and IATF 16949, and all products are qualified with Telcordia GR-468 and GR-1221-CORE reliability test.


The company currently has seven dedicated laboratories and is equipped with many high precision instruments, to ensure excellent reliability of our products. We have built an optical precision processing center and a machining center, manufacturing crystals, mirrors, PBS, other flat surface optics and mechanical components in-house, the key material production capability makes us more competitive.

We strive to continuously improve our products with proactive, data driven, quality first systems and processes.




## Thin-Film LiNbO<sub>3</sub> Products

|                |  |
|----------------|--|
| HB-CDM-130G    | C+L Band 130 GBaud Coherent Driver Modulator       |
| AM70           | C+L Band 70 GHz Intensity Modulator                |
| TFLN 40G-IQ    | 40 GHz TFLN IQ Modulator                           |
| 800 Gb/s PAM-4 | O-Band Thin-Film LiNbO <sub>3</sub> Modulator Chip |




## Bulk LiNbO<sub>3</sub> Products

|                 |   |
|-----------------|---|
| F10             | C-Band 10 GHz High Bandwidth Zero-Chirp Modulator         |
| AM20-XT/AM40-XT | C-Band 20/40 GHz Extended Temperature Intensity Modulator |
| PM10-C          | C-Band 10 GHz Phase Modulator                             |
| 40G-IQ-XT       | C-Band 20 GHz x 2 Extended Temperature IQ Modulator       |
| PM0.2-1060-XT   | 1060 nm 0.2 GHz Extended Temperature Phase Modulator      |
| PM2.5-1060-XT   | 1060 nm 2.5 GHz Extended Temperature Phase Modulator      |
| PM10-1060-XT    | 1060 nm 10 GHz Extended Temperature Phase Modulator       |



## C+L Band 130 GBaud Coherent Driver Modulator (HB-CDM-130G)

AFR's HB-CDM-130G is a Quad-Channel 130 GBaud High-Bandwidth coherent driver modulator integrated with an RF driver, based on Thin-Film LiNbO<sub>3</sub> chip. It is designed for 400/800 Gb/s and above coherent optical transport systems and transceivers, with Baud rate over 130G per channel.



### Features

- Support Coherent Transmission at Baud Rate of up to 130 GBaud
- C/C++ Band, and L/L++ Band Available
- Electro-Optic Bandwidth: 65 GHz
- Optical Extinction Ratio ≥ 23 dB
- Power Consumption < 3.5 W
- Compatible with OIF-HB-CDM-02.0 IA Class 80 - Type 3
- Standard Form Factor Module 30 x 12 x 4.5 mm

### Applications

- DP-QPSK Coding
- DP-16QAM Coding



## C+L Band 70 GHz Intensity Modulator (AM70)

AFR's Thin-Film LiNbO<sub>3</sub> intensity modulators that expand the performance of traditional LiNbO<sub>3</sub> modulators combining much lower driving voltage and smaller footprint while extending the bandwidth above 65 GHz. The increasing demand to shift the transmission frequency in analog fiber optic links towards higher frequency finds in AFR analog modulators the most advanced and suitable answer. The experience and know-how of AFR engineers is available to customize our products to the customer's specific requirements.



### Features

- X-Cut Thin-Film LiNbO<sub>3</sub> Waveguides
- Operating Wavelength at 1530 - 1610 nm
- Electro-Optic Bandwidth > 65 GHz
- Low Drive Voltage
- Optical Extinction Ratio ≥ 25 dB
- Single-End Drive

### Applications

- Digital/Analog Transmission
- High Frequency Fiber Optic Links
- Instrumentation
- RoF





## 40 GHz TFLN IQ Modulator

The 40G-Thin Film modulator design is based on a dual parallel structure of 2 Mach-Zehnder modulators embedded in a Mach-Zehnder super-structure. Each internal modulator is designed to have EO bandwidth above 20 GHz. Monitor photodiode is provided for automatic bias control.



### Features

- Thin Film X-Cut Lithium Niobate
- Operating at C-Band
- Electro-Optic Bandwidth > 25 GHz
- Compliance with Telcordia GR-468-CORE
- Hermetically Sealed
- Excellent Linearity

### Applications

- OFDM Coding
- QPSK Coding
- QAM Coding
- CS-SSB (Carrier Suppressed Single Side Band)
- FMCW LiDAR in Autonomous Driving




## O-Band Thin-Film LiNbO<sub>3</sub> Modulator Chip (800 Gb/s PAM-4)



With the cutting-edge Thin-Film LiNbO<sub>3</sub> technology, AFR's PAM-4 modulator products support intra data center and data center interconnect at data rate of 800 Gb/s, 1.6Tb/s and beyond, enabling optical I/Os for ultra-high bandwidth switches at 25.6T, 51.2T, 102.4T and beyond.

AFR's PAM-4 product portfolio includes DR4, DR8, FR4 and 2xFR4 modulator chips and Sub-Assemblies for QSFP-DD, OSFP and OSFP-XD optical modules, with low drive voltage and low insertion loss at data rate of 800 Gb/s and above.

### Applications of AFR's PAM-4 Chip: QSFP-DD/OSFP/OSFP-XD Type Transceiver Modules



### Ordering Information


Please contact AFR sales for customized PAM-4 modulator products.

## C-Band 10 GHz High Bandwidth Zero-Chirp Modulator (F10)

AFR High Bandwidth Zero-Chirp F10 modulators are based on the Mach-Zehnder Interferometer (MZI) architecture. They are manufactured using the highly reliable titanium indiffusion technology in X-Cut, Y-Propagating LiNbO<sub>3</sub> substrates. The F10 is a single drive modulator designed for high bit rate advanced metro to long haul communication systems that requires the superior performance. The F10 modulator contains an integrated photo detector that may be used to set and lock the DC bias on the modulator as well as provide an estimate of the modulator output optical power.

### Features

- Titanium-Indiffused Waveguide
- X-Cut LiNbO<sub>3</sub>
- Electro-Optic Bandwidth > 12.5 GHz
- Optical Insertion Loss < 4.5 dB
- RF V<sub>π</sub> Voltage: 5 V (typ. @ 1 kHz)
- Integrated Monitor Photodiode
- Integrated Polarizer
- Compliance with Telcordia GR-468-CORE





### Applications

- External Intensity Modulation NRZ and RZ
- High Frequency RF Signal Over Fiber Optic Links
- Instrumentation

### Optical and Electrical Specifications


| Parameter                               | Conditions   | Min  | Typ | Max  | Unit |
|---|--|------|-----|------|------|
| <b>Optical</b>                          |  |      |     |      |      |
| Operating Wavelength                    | -  | 1525 | -   | 1570 | nm   |
| Insertion Loss                          | w/o connector  | -    | -   | 4.5  | dB   |
| Extinction Ratio                        | @ DC   | 20   | 24  | -    | dB   |
| Maximum Optical Input Power             | CW   | -    | -   | 100  | mW   |
| PRBS Eye Extinction Ratio               | 10.7 Gb/s PRBS 2 <sup>31</sup> -1  | 13   | -   | -    | dB   |
| <b>Electrical - RF Port</b>             |  |      |     |      |      |
| S <sub>21</sub> Electro-Optic Bandwidth | - 3 dB, 130 MHz  | 11   | -   | -    | GHz  |
| Bandwidth Ripple                        | 130 MHz - 12.5 GHz   | - 1  | -   | 1    | dB   |
| S <sub>11</sub> Electrical Return Loss  | 130 MHz - 12.5 GHz   | 10   | 11  | -    | dB   |
| RF V <sub>π</sub> Voltage               | @ 1 kHz  | -    | 5   | 6.5  | V    |
| <b>Electrical - Bias Port</b>           |  |      |     |      |      |
| Bias V <sub>π</sub> Voltage             | @ 1 kHz  | -    | 5.5 | 6.0  | V    |
| <b>Pinout and Fiber Specifications</b>  |  |      |     |      |      |
| RF Connector                            | GPO male   |      |     |      |      |
| Input Fiber                             | Corning PM15-U25D or PM15-U40D (Panda Fiber), > 1.0 m, 900 μm loose tube fiber |      |     |      |      |
| Output Fiber                            | Corning SMF-28™ or PM15-U25D (Panda Fiber), > 1.0 m, 900 μm loose tube fiber   |      |     |      |      |

### Performance Characteristics



## C-Band 10 GHz High Bandwidth Zero-Chirp Modulator (F10)

### Package Dimensions



\* All dimensions measured in mm. L1 is fiber length with 900 μm loose tube. L2 is length of bare fiber.

### Pinout Information

| Pin | Name | Description            |
|-----|------|------------------------|
| 1   | PD-C | Photodiode Cathode (-) |
| 2   | PD-A | Photodiode Anode (+)   |
| 3   | Bias | MZ DC Bias Voltage     |
| 4   | GND  | Ground                 |
| RF  | -    | RF Input (GPO male)    |

### Ordering Information

#### 103076200010

F10, C-band 10 GHz High Bandwidth Zero-Chirp LiNbO<sub>3</sub> Intensity Modulator (Black) Corning PM15-U40D, (Blue) Corning SMF-28TM, > 1.1 m, 900 μm PMF/SMF loose tube fiber

#### 103076200007

F10, C-band 10 GHz High Bandwidth Zero-Chirp LiNbO<sub>3</sub> Intensity Modulator (Black) Corning PM15-U25D, > 1.1 m, 900 μm PMF/PMF loose tube fiber

#### 103076200013

F10, C-band 10 GHz High Bandwidth Zero-Chirp LiNbO<sub>3</sub> Intensity Modulator (Black) Corning PM15-U40D, > 1.0 m, 900 μm PMF/PMF loose tube fiber

## C-Band 20/40 GHz Extended Temperature Intensity Modulator (AM20-XT/AM40-XT)

AFR Broadband Analog Intensity Modulators combine high linearity with low driving voltage and small footprint, covering frequency range from 20 GHz to beyond 40 GHz (AM20-XT: 20 - 30 GHz; AM40-XT: > 30 GHz). The experience and know-how of AFR engineers is available to customize our products to the customer's specific requirements.



### Features

- Titanium Indiffused Waveguides
- X-Cut LiNbO<sub>3</sub>
- Operating at C+L-Band
- Electro-Optic Bandwidth > 32 GHz
- Low Drive Voltage Compatible with Commercially Available Drivers
- Low Optical Insertion Loss
- Integrated Photodiode
- Integrated Polarizer
- Hermetically Sealed
- Operating and Storage Temperature at - 55 to + 85°C

### Applications

- Digital/Analog Transmission
- High Frequency RF over Fiber Optic Links
- Delay Lines Systems
- Instrumentation



## C-Band 20/40 GHz Extended Temperature Intensity Modulator (AM20-XT/AM40-XT)

### Optical and Electrical Specifications

| Parameter                     | Conditions      | Value (AM20-XT) | Value (AM40-XT) | Unit |
|-------------------------------|-----------------|-----------------|-----------------|------|
| <b>Optical</b>                |                 |                 |                 |      |
| Operating Wavelength          | -               | 1525 - 1615     | 1525 - 1615     | nm   |
| Insertion Loss                | No connectors   | < 4.5 (3.5 typ) | < 5.0 (4.0 typ) | dB   |
|                               | With connectors | < 5.0 (4.0 typ) | < 5.5 (4.5 typ) |      |
| Optical Return Loss           | No connectors   | > 45            | > 45            | dB   |
| Polarization Extinction Ratio | -               | > 20 (23 typ)   | > 20 (23 typ)   | dB   |

### Electrical – RF Port

|   |                 |                        |                        |      |
|---|-----------------|------------------------|------------------------|------|
| S <sub>21</sub> Electro-Optic Bandwidth | - 3 dBe         | > 20 (23 typ)          | > 30 (31 typ)          | GHz  |
| S <sub>11</sub> Electrical Return Loss  | 40 MHz – 20 GHz | < - 10 (- 12 typ)      | < - 10 (- 12 typ)      | dB   |
|   | 20 GHz – 35 GHz | -                      | < - 8 (- 10 typ)       | -    |
| RF V <sub>π</sub> Voltage               | @ 1 kHz         | < 5.0 (4.5 typ)        | < 5.2 (4.7 typ)        | V    |
|   | @ 20 GHz        | 6.0                    | 6.0                    | V    |
| RF Impedance                            | -               | 50                     | 50                     | Ω    |
| Bias V <sub>π</sub> Voltage             | @ 1 kHz         | < 5.5 (5.0 typ)        | < 5.5 (5.0 typ)        | V    |
| Bias Impedance                          | @ DC            | 1                      | 1                      | MΩ   |
| Photodiode Responsivity                 | -               | > 1 x 10 <sup>-3</sup> | > 1 x 10 <sup>-3</sup> | mA/W |
| Linearity                               | -               | ± 10%                  | ± 10%                  | -    |

### Pinout and Fiber Specifications


|                       |   |
|-----------------------|---|
| RF Connector          | V-Connector   |
| Bias and PD Connector | LEAD pins   |
| Input Fiber           | Corning/Fujikura SM15P UV/UV250 (Panda Fiber), > 1.3 m, 900 μm loose tube fiber |
| Output Fiber          | Corning/Fujikura SM15P UV/UV250 (Panda Fiber), > 1.3 m, 900 μm loose tube fiber |

### Absolute Maximum Ratings

| Parameter                                    | Conditions         | Min  | Max   | Unit   |
|--|--------------------|------|-------|--------|
| Maximum RF Input Power                       | RF port AC coupled | -    | 25    | dBm    |
| Maximum Optical Input Power                  | CW                 | -    | 100   | mW     |
| Operating Case Temperature                   | AM20-XT/AM40-XT    | - 55 | + 85  | °C     |
| Storage Temperature                          | AM20-XT/AM40-XT    | - 55 | + 85  | °C     |
| Maximum Operating Temperature Variation Rate | AM20-XT/AM40-XT    | -    | 10    | °C/min |
| Operating Humidity                           | -                  | 5    | 85    | %      |
| Leads Soldering Temperature                  | -                  | -    | + 250 | °C     |
| Leads Soldering Time                         | -                  | -    | 10    | s      |

## C-Band 20/40 GHz Extended Temperature Intensity Modulator (AM20-XT/AM40-XT)

### Mechanical Outline



\* AM20-XT and AM40-XT have same footprints. All dimensions measured in mm. L1 is fiber length with 900  $\mu$ m loose tube. L2 is length of bare fiber.

### Pinout Information

| Pin | Name | Description           |
|-----|------|-----------------------|
| 1   | RF   | RF input, V-connector |
| 2   | GND  | Ground                |
| 3   | Bias | Bias Voltage          |
| 4   | PD-C | Photodiode cathode    |
| 5   | PD-A | Photodiode anode      |

### Ordering Information

**103076200001**


AM20-XT, C-Band 20 GHz Extended Temperature Intensity Modulator  
(> 1.3 m, 900  $\mu$ m PMF/PMF loose tube fiber)

**103076200004**

AM40-XT, C-Band 40 GHz Extended Temperature Intensity Modulator  
(> 1.3 m, 900  $\mu$ m PMF/PMF loose tube fiber)

## C-Band 10 GHz Phase Modulator (PM10-C)

AFR broadband phase modulators combine high linearity with low driving voltage and small footprint, covering all the frequency range up to 10 GHz.




### Features

- Titanium-Indiffused Waveguide
- Z-Cut LiNbO<sub>3</sub>
- Frequency Response up to 10 GHz
- Low Optical Insertion Loss

### Applications

- FM Spectroscopy
- Frequency Shifting
- Laser Linewidth Broadening
- Laser Beam Combining
- Quantum Key Distribution
- Interferometric Fiber Sensing

### Performance Characteristics





C-Band 10 GHz Phase Modulator (PM10-C)

Optical and Electrical Specifications

| Parameter                   | Conditions      | Min  | Typ | Max  | Unit |
|-----------------------------|-----------------|------|-----|------|------|
| <b>Optical</b>              |                 |      |     |      |      |
| Operating Wavelength Range  | -               | 1530 | -   | 1565 | nm   |
| Insertion Loss, IL          | No connectors   | -    | 2.5 | 3.5  | dB   |
|                             | With connectors | -    | 3.0 | 4.0  |      |
| Optical Return Loss, RL     | No connectors   | -    | 45  | -    | dB   |
| Polarization Dependent Loss | -               | -    | 10  | -    | dB   |

Electrical

|   |          |    |      |      |     |
|---|----------|----|------|------|-----|
| S <sub>21</sub> Electro-optic Bandwidth | - 3 dBe  | 10 | 12   | -    | GHz |
| ΔS <sub>21</sub> Ripple                 | -        | -  | 0.5  | 1.0  | dB  |
| S <sub>11</sub> Electrical Return Loss  | -        | -  | - 15 | - 10 | dB  |
| RF V <sub>π</sub> Voltage               | @ 50 kHz | -  | 4    | 5    | V   |
|   | @ 10 GHz | -  | 6    | 7    |     |
| RF Input Impedance                      | -        | -  | 50   | -    | Ω   |

Pinout and Fiber Specifications

|              |   |
|--------------|---|
| RF Connector | GPO male  |
| Ground       | LEAD pins   |
| Input Fiber  | Corning/Fujikura SM15P UV/UV250 (Panda Fiber), > 1.5 m, 900 μm loose tube fiber |
| Output Fiber | Corning/Fujikura SM15P UV/UV250 (Panda Fiber), > 1.5 m, 900 μm loose tube fiber |


Absolute Maximum Ratings

| Parameter                                    | Conditions         | Min  | Max   | Unit   |
|--|--------------------|------|-------|--------|
| Maximum Input Power (Electrical)             | RF port AC coupled | -    | 28    | dBm    |
| Maximum Input Power (Optical)                | CW                 | -    | 20    | dBm    |
| Operating Case Temperature                   | -                  | 0    | + 70  | °C     |
| Storage Temperature                          | -                  | - 40 | + 85  | °C     |
| Maximum Operating Temperature Variation Rate | -                  | -    | 1     | °C/min |
| Operating Humidity                           | -                  | 5    | 85    | %      |
| Leads Soldering Temperature                  | -                  | -    | + 250 | °C     |
| Leads Soldering Time                         | -                  | -    | 10    | s      |

\* All requirements at Top = 25 °C, wavelength 1550 nm and BOL unless otherwise specified.

C-Band 10 GHz Phase Modulator (PM10-C)

Mechanical Outline



\* All dimensions measured in mm. L1 is fiber length with 900 μm loose tube. L2 is length of bare fiber.

Pinout Information

| Pin | Name | Description         |
|-----|------|---------------------|
| 1   | GND  | Ground              |
| 2   | GND  | Ground              |
| 3   | GND  | Ground              |
| 4   | GND  | Ground              |
| RF  | -    | RF Input (GPO male) |


Ordering Information

103076100001

PM10-C, C-Band 10 GHz LiNbO<sub>3</sub> Phase Modulator,  
(> 1.5 m, 900 μm PMF/PMF loose tube fiber)

## C-Band 20 GHz x 2 Extended Temperature IQ Modulator (40G-IQ-XT)

The 40G-IQ-XT modulator design is based on a dual parallel structure of two Mach-Zehnder modulators embedded in a Mach Zehnder super-structure. Each internal modulator is designed to have EO bandwidth above 20 GHz. Monitor photodiode is provided for automatic bias control. The 40G-IQ-XT version is provided extended operating temperature at - 55 to + 85°C for different environmental applications.





### Features

- Titanium-Indiffused Waveguide
- X-Cut LiNbO<sub>3</sub>
- Electro-Optic Bandwidth > 30 GHz
- Low Optical Insertion Loss
- Compliance with Telcordia GR-468-CORE
- Extended Operating Temperature at - 55 °C to + 85 °C
- Hermetically Sealed
- Excellent Linearity

### Applications

- OFDM Coding
- QPSK Coding
- QAM Coding
- CS-SSB (Carrier Suppressed Single Side Band)
- FMCW LiDAR in Autonomous Driving

### Performance Characteristics



## C-Band 20 GHz x 2 Extended Temperature IQ Modulator (40G-IQ-XT)

### Specifications

| Parameter   | Conditions   | Min     | Typ      | Max  | Unit   |
|---|--|---------|----------|------|--------|
| <b>Optical</b>  |  |         |          |      |        |
| Operating Wavelength Range  | -  | 1525    | -        | 1570 | nm     |
| Insertion Loss, IL  | EOL, - 5 to + 75 °C, over C-Band   | -       | 5.0      | 7.0  | dB     |
| Phase-MZI Optical Extinction Ratio @ DC                                       | -  | 24      | -        | -    | dB     |
| RF-MZI Optical Extinction Ratio @ DC  | -  | 24      | 29       | -    | dB     |
| PER   | -  | 20      | -        | -    | dB     |
| Optical Return Loss, RL   | Input & Output   | 40      | -        | -    | dB     |
| Maximum Input Power (Optical)   | CW   | -       | -        | 100  | mW     |
| <b>Electrical RF Ports</b>  |  |         |          |      |        |
| RF-MZI V <sub>π</sub> Voltage   | @ 1 kHz  | -       | 5.0      | 7.0  | V      |
| RF-MZO - 3 dB E/O Bandwidth   | wrt. 2 GHz   | 20      | 23       | -    | GHz    |
| RF-MZI S <sub>21</sub> Flatness   | 300 MHz – 20 GHz   | - 1     | -        | 1    | dB     |
| Amplitude Difference Between - MZIs (Difference between two S <sub>21</sub> ) | -  | - 1     | -        | 1    | dB     |
| RF Delay Between RF-MZIs  | -  | - 5     | -        | 5    | ps     |
| RF-MZI Electrical Return Loss S <sub>11</sub>                                 | 40 MHz – 17 GHz<br>17 GHz – 30 GHz   | 10<br>8 | 12<br>10 | -    | dB     |
| <b>Electrical Bias Ports</b>  |  |         |          |      |        |
| RF MZI Bias V <sub>π</sub> Voltage  | @ 1 kHz  | -       | 7        | 8    | V      |
| Phase MZI Bias V <sub>π</sub> Voltage   | @ 1 kHz  | -       | 7        | 8    | V      |
| RF and Phase MZI Bias V <sub>π</sub> Voltage Variation Over Wavelength        | 1550 nm  | - 5     | -        | 5    | %      |
| Bias Port Impedance   | @ DC   | 1       | -        | -    | MΩ     |
| <b>Monitor Photodiode</b>   |  |         |          |      |        |
| Responsivity  | -  | 20      | -        | 120  | mA/W   |
| Linearity   | -  | - 10    | -        | 10   | %      |
| Phase Error   | PD is not inverting  | - 5     | -        | 5    | Degree |
| <b>Pin-Out and Fiber Specifications</b>                                       |  |         |          |      |        |
| RF Connector  | SMPM male  |         |          |      |        |
| Bias Ports  | DC pins  |         |          |      |        |
| Input Fiber   | Polarization Maintaining Fiber, PMF - Panda (Corning/Fujikura PM15-U25D), > 1.5 m, 900 μm loose tube fiber |         |          |      |        |
| Output Fiber  | Polarization Maintaining Fiber, PMF - Panda (Corning/Fujikura PM15-U25D), > 1.5 m, 900 μm loose tube fiber |         |          |      |        |


### Absolute Maximum Ratings

| Parameter                          | Conditions         | Min  | Max  | Unit               |
|------------------------------------|--------------------|------|------|--------------------|
| Maximum Input Power (Electrical)   | RF port AC coupled | -    | 10   | V <sub>pk-pk</sub> |
| DC Voltage at DC Port              | -                  | - 40 | 40   | V                  |
| Monitor Photodiode Reverse Current | -                  | -    | < 2  | mA                 |
| Monitor Photodiode Forward Current | -                  | -    | < 10 | mA                 |
| Monitor Photodiode Reverse Voltage | -                  | -    | < 15 | V                  |
| Operating Case Temperature         | 40G-IQ-XT          | - 55 | + 85 | °C                 |
| Maximum Top Variation Rate         | 40G-IQ-XT          | -    | 10   | °C/min             |
| Storage Temperature                | 40G-IQ-XT          | - 55 | + 85 | °C                 |
| Operating Humidity                 | Non-Condensing     | 5    | 85   | %                  |



C-Band 20 GHz x 2 Extended Temperature IQ Modulator (40G-IQ-XT)

Mechanical Outline



\* All dimension measured in mm.

Pin-Out Information

| Pin | Name/Description | Note                 |
|-----|------------------|----------------------|
| 1   | RF. 1            | RF Input (SMPM male) |
| 2   | RF. 2            | RF Input (SMPM male) |
| 3   | BIAS 2+          | Bias wrt RF.2 +V     |
| 4   | BIAS 2-          | Bias wrt RF.2 -V     |
| 5   | BIAS 1+          | Bias wrt RF.1 +V     |
| 6   | BIAS 1-          | Bias wrt RF.1 -V     |
| 7   | Bias PH+         | Bias Phase +V        |
| 8   | Bias PH-         | Bias Phase -V        |
| 9   | PD Cathode       | - ve                 |
| 10  | PD Anode         | + ve                 |
| 11  | GND              | Ground               |

Note: The pin# 3&4, 5&6, 7&8 pin pair doesn't need to be exact as above table, but any pin pair need to be of opposite voltage.


Ordering Information

103076300008

40G-IQ-XT, C-Band 20 GHz x 2 Extended Temperature IQ Modulator (>1.4 m, 900 μm PMF/PMF loose tube fiber )

PM0.2-1060-XT/PM2.5-1060-XT/PM10-1060-XT Phase Modulator

AFR Broadband Phase Modulator combines high linearity with low driving voltage and small footprint, covering frequency range from DC up to 10 GHz. The extended operating temperature range given this series of phase modulators can operate at different environmental applications.



Features

- APE Waveguide
- Z-Cut LiNbO<sub>3</sub>
- Operating Wavelength Range 950 - 1150 nm
- Low Drive Voltage Compatible with Commercially Available Drivers
- Low Optical Insertion Loss
- Frequency Response up to 0.2 GHz (PM0.2-1060-XT)
- Frequency Response up to 2.5 GHz (PM2.5-1060-XT)
- Frequency Response up to 10 GHz (PM10-1060-XT)
- Extended Operating Temperature at - 55 to + 85°C
- Hermetically Sealed

Applications

- Ultra-Fast High-Power Lasers
- Phase Shifting
- Laser Linewidth Broadening
- Laser Beam Combining

Optical and Electrical Specifications

| Parameter                   | Conditions       | Min  | Typ | Max       | Unit |
|-----------------------------|------------------|------|-----|-----------|------|
| <b>Optical</b>              |                  |      |     |           |      |
| Operating Wavelength Range  | -                | 1025 | -   | 1090      | nm   |
| Insertion Loss, IL          | Standard/Premium | -    | -   | 3.0 / 2.0 | dB   |
| Optical Return Loss, RL     | -                | 40   | 45  | -         | dB   |
| Polarization Dependent Loss | -                | 25   | 30  | -         | dB   |

Electrical

|   |                         |     |     |      |     |
|---|-------------------------|-----|-----|------|-----|
| S <sub>21</sub> Electro-optic Bandwidth | PM0.2-1060-XT @ - 3 dBe | 0.2 | -   | -    | GHz |
|   | PM2.5-1060-XT @ - 3 dBe | 2.5 | -   | -    |     |
|   | PM10-1060-XT @ - 3 dBe  | 10  | -   | -    |     |
| ΔS <sub>21</sub> Ripple                 | -                       | -   | 0.5 | 1.0  | dB  |
| S <sub>11</sub> Electrical Return Loss  | -                       | -   | -   | - 10 | dB  |
| V <sub>r</sub> RF Voltage               | PM0.2-1060-XT @ 50 kHz  | -   | -   | 2    | V   |
|   | PM2.5-1060-XT @ 50 kHz  | -   | -   | 2    |     |
|   | PM10-1060-XT @ 50 kHz   | -   | -   | 2    |     |
| RF Input Impedance                      | -                       | -   | 50  | -    | Ω   |

Pinout and Fiber Specifications

|                            |   |
|----------------------------|---|
| RF Connector               | 2.92 mm Female K connector  |
| Input Fiber & Output Fiber | Corning PM98-U25D (PM980), > 1.5 m, 900 μm PMF/PMF loose tube fiber |

\* Without optical connectors


# Bulk LiNbO<sub>3</sub> Products

## PM0.2-1060-XT/PM2.5-1060-XT/PM10-1060-XT Phase Modulator

### Absolute Maximum Ratings

| Parameter                        | Conditions         | Min  | Max  | Unit |
|----------------------------------|--------------------|------|------|------|
| Maximum Input Power (Electrical) | RF port AC coupled | -    | 33   | dBm  |
| Maximum Input Power (Optical)    | CW                 | -    | 25   | dBm  |
| Operating Case Temperature       | -                  | - 55 | + 85 | °C   |
| Storage Temperature              | -                  | - 55 | + 85 | °C   |
| Operating Humidity               | -                  | 5    | 85   | %    |

### Mechanical Outline



\* All dimension measured in mm.

### Ordering Information

#### 103076100010

PM0.2-1060-XT, 1060 nm 0.2 GHz LiNbO<sub>3</sub> Phase Modulator  
(Corning PM98-U25D (PM980), > 1.5 m, 900 μm PMF/PMF loose tube fiber)

#### 103076100011

PM2.5-1060-XT, 1060 nm 2.5 GHz LiNbO<sub>3</sub> Phase Modulator  
(Corning PM98-U25D (PM980), > 1.5 m, 900 μm PMF/PMF loose tube fiber)

#### 103076100012

PM10-1060-XT, 1060 nm 10 GHz LiNbO<sub>3</sub> Phase Modulator  
(Corning PM98-U25D (PM980), > 1.5 m, 900 μm PMF/PMF loose tube fiber)



Brochure version: Mar, 2025

Every effort has been made to ensure the accuracy of the information contained in this catalog at the time of publication. As part of our policy of continuous product improvement, we reserve the right to change specifications at any time. For the most up-to-date information, please refer to our website.

[www.fiber-resources.com](http://www.fiber-resources.com)